

OVER 15 YEARS EXPERIENCE

LINEAR

LUX

LED LIGHTING SOLUTIONS

EXPERT ADVICE

**PROFESSIONAL
PRODUCTS**

**COMPLETE
SOLUTIONS**

GO TO OUR WEBSITE FOR
STOCK AVAILABILITY, DATA
SHEETS AND PRICING

WE MANUFACTURE LED
LINEAR LIGHTS TO YOUR
SPECIFICATIONS USING ANY
OF OUR ALUMINIUM PROFILES
OF ANY LENGTH UP TO 3m



**13 Jaybel St
Salisbury Q. 4107**

linearlux.com.au

mail@linearlux.com.au

0434 326 000

**FLEXIBLE
LED STRIP
LIGHT**

DRIVERS

CONTROLLERS

PROFILE

**CUSTOM
LED LINEAR
LIGHTS**

**POWER
SUPPLIES**

**SMART
OUTDOOR
LIGHTS**

COMMERCIAL
QUALITY
LONG-LIFE
CONSISTANT
COLOUR (CCT)

FLEXIBLE LED STRIP LIGHT SELECTION GUIDE



Electrical Data							
Voltage	12.0 VDC	12.0 VDC	24.0 VDC	12.0 / 24.0 VDC	24.0 VDC	24.0 VDC	24.0 VDC
Wattage per metre	4.8W	9.6W	14.4W	14.4W	24W	17.1W	26.4W
Current per metre	0.4 A / 12 V	0.8 A / 12 V	0.6 A / 24 V	1.2 A / 12 V 0.6 A / 24 V	1.0 A / 24 V	0.71 A / 24 V	1.1 A / 24 V

LED Data							
LED type	3528	3528	2016	2835	2835	5050 RGB	5050 RGB 2016 CW+WW
Manufacturer	Dilux	Dilux	Dilux	Dilux	Dilux	Dilux	Dilux
No. of chips per LED	1	1	1	1	1	3	3 1
No. of LEDs per metre	60	120	120	120	240	84	60 120
LED pitch	16.67 mm	8.35 mm	8.35 mm	8.35 mm	4.17 mm	11.9 mm	16.67 mm

Photometric Data							
Colour temperature	3,000 4,000 6,000°K	3,000 4,000 6,000°K	3,000 4,000 6,000°K	2,400 3,000 4,000 6,000°K	3,000 4,000 6,000°K	Red, Green & Blue	Red, Green & Blue + 2,450~6100°K
Colour rendering index RA	>80	>80	>90	>80	>80	N/A	>90 (2016)
Luminous flux per metre	450 lm >3,700°K 420 lm >3,200°K	900 lm >3,700°K 840 lm >3,200°K	1,260 lm >3,700°K 1,200 lm >3,200°K	1,680 lm >3,700°K 1,500 lm >3,200°K	2,880 lm >3,700°K 2,520 lm >3,200°K	126 lm Red, 504 lm Green 84 lm Blue	90 lm Red, 360 lm Green 60 lm Blue 480 lm 2,450°K 600 lm 6,000°K
Luminous efficacy	93.75 lm/W >3,700°K	93.75 lm/W >3,700°K	87.5 lm/W >3,700°K	117 lm/W >3,700°K	120 lm/W >3,700°K	-	-

Construction / Protection Data							
Substrate	Double layer PPCB	Double layer PPCB	Double layer PPCB	Double layer PPCB	Double layer PPCB	Double layer PPCB	Double layer PPCB
Thickness of FPCB	2 oz	2 oz	2 oz	2 oz	2 oz	2 oz	3 oz
IP Rating	20, 54, 67	20, 54, 67	20, 54, 67	20, 54, 67	20, 54	20, 54, 67	20, 54, 67

Dimensions							
Thickness of FPCB	3 LEDs / 50mm (12V)	3 LEDs / 25mm (12V)	6 LEDs / 50mm (24V)	3 LEDs / 25mm (12V) 6 LEDs / 50mm (24V)	6 LEDs / 25mm (24V)	6 LEDs / 71.4mm (24V)	18 LEDs / 100mm (24V)
Length	5,000mm	5,000mm	5,000mm	5,000mm	5,000mm	5,000mm	5,000mm
Width	8.0mm	8.0mm	5.0mm	8.0mm	10.0mm	10.0mm	10.0mm
Height	2.1mm	2.1mm	1.0mm	1.2mm	1.2mm	1.8mm	1.8mm

CONTROLLERS

WIRELESS REMOTES



DIMMER WALLPLATE



CCT (2 COLOUR) WALLPLATE



RGB / RGBW WALLPLATE



RGB+CCT WALLPLATE


WIRELESS WALLPLATES



DIMMER WALLPLATE



CCT (2 COLOUR) WALLPLATE



RGB / RGBW WALLPLATE



RGB+CCT WALLPLATE

WIRELESS RECEIVERS



DIMMER + CCT RECEIVER



RGB / RGBW RECEIVER



RGB+CCT RECEIVER



UNIVERSAL RECEIVER

EXPANSION MODULES

SIGNAL CONVERTERS



AMPLIFIER / EXTENDER



WIFI GATEWAY



**0/1-10V &
PUSH BUTTON DIMMER**



DALI SINGLE CONTROLLER



DALI 5CH CONTROLLER

POWER SUPPLIES

CONSTANT VOLTAGE LED DRIVERS



All drivers are Australian Approved & fitted with Australian mains plug

Adj V

Allows the output voltage to be adjusted by +/- 10%

Wallplate Triac Dimmable

Dimmable by the use of either a standard trailing or leading edge dimmer

3 in 1 Dimmable

Dimmable by the following methods:

- 0~10Vdc
- 10V PWM signal
- Resistance



AUTHORISED RESELLER

25~240W



ADAPTOR

120~1,600W



BATTERY CHARGER

15W~10KW



ENCLOSED

1, 2 & 3ph
10~960W
AC-DC
DC-DC
UPS



DIN RAIL

0.5~1,000W










DC-DC CONVERTERS

THIS IS A SELECTION OF POPULAR DRIVERS FROM OUR MUCH LARGER STOCKED RANGE

	VOLTAGE	WATTAGE	AMPS	ADJ V	DIMMABLE	DIMENSIONS L W H (mm)
PLN-30-12	12V	30W	2.5A	NO	NO	145x47x30
PLN-30-24	24V	30W	1.25A	NO	NO	IP64 3YR WTY
PDV-30-12	12V	30W	2.5A	NO	TRIAC	155x54x20
PDV-30-24	24V	30W	1.25A	NO	TRIAC	IP20 5YR WTY
PWM-40-12	12V	40W	3.3A	NO	3 in 1	150x53x35
PWM-40-24	24V	40W	1.7A	NO	3 in 1	IP67 5YR WTY
ELG-75-12	12V	75W	5A	NO	NO	180x63x36
ELG-75-12AB	12V	75W	5A	YES	3 in 1	IP67 IP65 (AB)
ELG-75-24	24V	75W	3.2A	NO	NO	5YR WTY
ELG-75-24AB	24V	75W	3.2A	YES	3 in 1	
PDV-75-12	12V	75W	6.3A	NO	TRIAC	155x54x20
PDV-75-24	24V	75W	3.1A	NO	TRIAC	IP20 5YR WTY
PWM-90-12	12V	90W	7.5A	NO	3 in 1	171x63x38
PWM-90-24	24V	90W	3.7A	NO	3 in 1	IP67 5YR WTY
PDV-100-12	12V	100W	8.3A	NO	TRIAC	230x70x43
PDV-100-24	24V	100W	4.1A	NO	TRIAC	IP66 5YR WTY
PWM-120-12	12V	120W	10A	NO	3 in 1	191x63x38
PWM-120-24	24V	120W	5A	NO	3 in 1	IP67 5YR WTY
ELG-150-12	12V	150W	10A	NO	NO	219x63x36
ELG-150-12AB	12V	150W	10A	YES	3 in 1	IP67 IP65 (AB)
ELG-150-24	24V	150W	6.2A	NO	NO	5YR WTY
ELG-150-24AB	24V	150W	6.2A	YES	3 in 1	
ELG-200-12	12V	200W	16A	NO	NO	244x71x38
ELG-200-12AB	12V	200W	16A	YES	3 in 1	IP67 IP65 (AB)
ELG-200-24	24V	200W	8.4A	NO	NO	5YR WTY
ELG-200-24AB	24V	200W	8.4A	YES	3 in 1	
PDV-200-12	12V	200W	16.6A	NO	TRIAC	265x78x47
PDV-200-24	24V	200W	8.3A	NO	TRIAC	IP66 5YR WTY
ELG-240-24	24V	240W	10A	NO	NO	244x71x38
ELG-240-24AB	24V	240W	10A	YES	3 in 1	IP67 IP65 (AB)
						5YR WTY
HLG-320H-12	12V	320W	22A	NO	NO	252x90x44
HLG-320H-12AB	12V	320W	22A	YES	3 in 1	IP67 IP65 (AB)
HLG-320H-24	24V	320W	13.3A	NO	NO	7YR WTY
HLG-320H-24AB	24V	320W	13.3A	YES	3 in 1	
HLG-600H-12	12V	600W	40A	NO	NO	280x144x49
HLG-600H-12AB	12V	600W	40A	YES	3 in 1	IP67 IP65 (AB)
HLG-600H-24	24V	600W	25A	NO	NO	7YR WTY
HLG-600H-24AB	24V	600W	25A	YES	3 in 1	

LED ALUMINIUM PROFILES

SUPPLIED IN 3m LENGTHS - HARDWARE INCLUDED



OUTDOOR LIGHTS

SMART OUTDOOR LIGHTS | RGB+CCT COLOUR CHANGING

CONTROLLED BY HANDHELD REMOTE, WIRELESS WALLPLATE, WIFI MOBILE APP & VOICE CONTROL

ONLY
2 WIRES



9 & 15W RGB+CCT GARDEN LIGHT

ONLY
3 WIRES



10W RGB+CCT FLOODLIGHT

ONLY
3 WIRES



5W RGB+CCT DECK LIGHT

ONLY
3 WIRES



9W RGB+CCT DECK LIGHT

SIGN MODULES



1.2W BACKLIGHT MODULE



3W EDGELIGHT MODULE



RGB BACKLIGHT 0.72W

SWITCHES & SENSORS

THIS IS A SMALL SELECTION OF AN EVER EXPANDING RANGE OF UNIQUE SWITCHES AND SENSORS. [SEE WEBSITE FOR MORE TYPES](#)



TOUCH DIMMER SWITCH




TOUCH DIMMER SWITCH
ILLUMINATED




DOOR OPEN/CLOSE SENSOR
HAND WAVE ON/OFF SENSOR



PIR SENSOR



LED PROFILE TOUCH DIM MODULE



LED PROFILE HAND WAVE DIM
MODULE



LED PROFILE PIR SENSOR MODULE

← THESE LED
PROFILE
MODULES
ARE
MOUNTED
WITHIN THE
ALUMINIUM
PROFILE