LL-PR-PLB-5615UDS

56x15



# **Finish**

Profile Colour	Clear Silver (Anodised) - stocked
	White (Painted) - indent*
	Black (Anodised) - indent*
	Custom Powder Coating - indent*
End Cap Colour	White - stocked
	Grey - indent*
	Black - indent*
	Silver - indent*

## **Light Transmission**

Lens (Cover)	Clear (100% light transmission) - indent*
	Opal (40~30% light transmission) - indent*
	Diffused (80~70% light transmission) - stocked
	Black - indent*



Profile	Aluminium: 6063-T5
	Anodised Thickness: $10\mu m$
Cover	Polycarbonate (fire rating: V2) UV Resistant
End Caps	Polycarbonate (fire rating: V2) UV Resistant
Pendant Kit	Stainless Steel

### **Dimensions**

Width (overall)	56.0 mm
Height (overall)	15.0 mm
Max LED tape width	14.0 mm
Length	3.0 m

## **Accessories**

Suspension Kit	None
End Caps	Blank & cable entry hole
Mounting Clips	None


<sup>\*</sup> Indent items are available but may incur minimum order quantities and long lead times. Please contact us.

## **ALUMINIUM FINISH**














# **COVER TYPES**


























© 2024, Linear Lux linearlux.au Data sheet issued August 2024 Page 2 of 2