#### CESSED GLED AN 40x16 LL-PR-RE-4016



#### Finish

_	
Profile Colour	Clear Silver (Anodised) - stocked
	White (Painted) - indent*
	Black (Anodised) - indent*
	Custom Powder Coating - indent*
End Cap Colour	White - stocked
	Grey - indent*
	Black - indent*
	Silver - indent*

### **Light Transmission**

Lens (Cover)	Clear (100% light transmission) - indent*
	Opal (40~30% light transmission) - stocked
	Diffused (80~70% light transmission) - indent*
	Black - stocked

#### Material

Profile	Aluminium: 6063-T5
	Anodised Thickness: 10µm
Cover	Polycarbonate (fire rating: V2) UV Resistant
End Caps	Polycarbonate (fire rating: V2) UV Resistant
Pendant Kit	Stainless Steel

#### **Dimensions**

Width (overall)	40.0 mm
Height (overall)	15.9 mm
Max LED tape width	11.0 mm
Length	3.0 m
Length	3.0 m

## Accessories

Suspension Kit	None
End Caps	Blank & cable entry hole
Mounting Clips	None

\* Indent items are available but may incur minimum order quantities and long lead times. Please contact us.

# **ALUMINIUM FINISH**










**COVER TYPES** 
















COC CE WOHS

© 2024, Linear Lux

linearlux.au